

mizu

Mizu Drift Wall Top Assemblies

IMPORTANT NOTE:

Wall top assemblies must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your product comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the product. The wall top assemblies are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS:

1. Check the breach is between 3-21mm from the finished wall
2. Check that the seats in the recess tap bodies are in good condition and free from foreign materials. Reseal if required
3. Separate the locknut and fibre washer from the cartridge
4. Grip the cartridge on the hexagonal flats and install the cartridge fully into breach until it comes to a firm stop. Do not tighten the cartridge into position by rotating the spindle
5. Turn spindle to the off position and turn on the water at the mains. Check that the cartridge has fully seated. If dripping occurs then gently tighten the cartridge further until dripping stops
6. Firmly tighten the cartridge locknut and fibre washer into position
7. Screw the bush connector onto the cartridge locknut
8. Place the wall flange and o-ring into position and screw the chrome bush cover onto the brass bush until it is tight against the wall
9. Turn cartridge spindles to the fully off position and assemble the handle
10. Ensure that the handle pins are pointing out to sides when in the off position
11. Fix the handle by tightening the grub screw with an allen key and then push the plug into position

For Basin Top Assemblies, follow steps 3-6, 9-11

CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions