DURA **VACUUM BREAKER**

SPECIFICATIONS	
Recommended use	The Dura vacuum breaker is a low hazard backflow device. It is a single chck valve spring loaded to a closed position with atmospheric vacuum breaker vent. They are generally attached to a hose tap to prevent backsyphonage, for example in the event of cross connevtion when filling a swimming pool. It can also be used in other applications including: laboratory sinks, service sinks, soap dispensers etc.
Working Pressure	1400kPa
Max. Working Temperature	80°C
Warranty	12 months
Installation	Installation is subject to the requirements of the applicable regulatory authority.
	Must have free ventilation at all times.
	Is not to be buried or installed into a pit.
	Shall not under normal operation be subject to constant pressure.
	Have no isolation valves located downstream of the vacuum breaker.
	For use with irrigation sprinkler heads less than 150mm above ground level. Install 450mm above the highest outlet.



PRODUCT RANGE AND DIMENSIONS	
Product Code	Description
1006796	Dura Vacuum Breaker to Suit 15mm Hosebib
1006797	Dura Vacuum Breaker to Suit 20mm Hosebib
1006798	Dura Vacuum Breaker to Suit 15mm Hosebib CP





DURA VACUUM BREAKER



REECE PRODUCT QUALITY GUARANTEE

You have purchased a quality product from Reece Australia Pty Ltd ABN 84 004 097 090 ("Reece"). This product is covered by a 12 month product warranty.

12 MONTH WARRANTY

This warranty covers faults in the product construction, material and assembly. Products which are within 12 months from the date of purchase, found upon inspection by an authorised Reece representative, to be defective in construction, material or assembly, will be repaired or exchanged with an equivalent product free of charge. Replaced items become Reece's property.

All replacement products will be available for collection without charge to the customer at the nearest Reece branch to the customer's location, or elsewhere as agreed between the customer and Reece.

Warranty Conditions

This warranty will apply only under all of the following conditions:

- The item has been installed by a licensed plumber
- Failure is due to a fault in the manufacture of the product
- Proof of purchase (including the date of purchase) is provided
- The installation of the product is in accordance with the instructions provided

This warranty does not cover products purchased as an exdisplay without being fully checked and tested for sale by the manufacturer.

This warranty does not include faults caused by:

- Unsuitable or improper use
- Incorrect installation or installation not in accordance with the instructions provided
- Installation or part installation by the purchaser or any person other than a LICENSED PLUMBER or tradesperson licensed to install this product.
- Normal wear and tear
- Inadequate or complete lack of maintenance
- · Chemical, electrochemical or electrical influences
- Harsh detergents or abrasive cleaners used on product finishes

EXCLUSIONS

To the fullest extent permitted by law, Reece excludes all liability for damage or injury to any person, damage to any property, and any indirect consequential or other loss or damage.

CLAIM PROCEDURE

For all warranty queries customers are to contact the branch where the product was purchased. These details can be found on your purchase invoice.

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

Plumbers/Contractors, please ensure a copy of the installation instructions is left with the end user for future reference.



