



Mizu Bloc MK2 Wall Basin Mixer Set Matte Black (4*)

IMPORTANT NOTE:

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS:

Mixers are recommended for use on mains pressure and instantaneous systems only. Equal pressure for hot and cold water supply is required for this single lever mixer.

1. Flush out new pipe work prior to connecting the new mixer
2. During installation, protect the exposed surface finish by using the plastic covers provided
3. In a typical installation, the mixer is mounted on a timber/metal noggin and secured using suitable screws through the mounting lugs
4. Connect mixer to hot and cold water supply
5. Pressure check all connections. Leaking joints are not covered by the warranty
6. When the wall is finished (eg. tiling), remove the protective covers and fit the cover plate, handle and basin outlet

SERVICING - REPLACEMENT OF CARTRIDGE:

1. Remove decorative cover (2) and unscrew the grub screw (3) using an allen key
2. Lift off the handle (1) and remove the cartridge dome (4), unscrew the brass locking nut (5) and lift out the cartridge (6)
3. Replace the cartridge (6), replace the brass locking nut (5), replace the cartridge dome (4) and replace the handle (1)
4. Tighten the grub screw (3) and push in decorative cover (2)

CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions