



Mizu Bloc MK2 Extended Basin Mixer Matte Black (4*)

IMPORTANT NOTE:

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

INSTALLATION INSTRUCTIONS:

1. Flush out new pipe work prior to connecting the new mixer
2. All mixers should be installed with isolating stop cocks (Arco)
3. This tap is suitable for high pressure applications where both hot and cold water supply pressures are at 150kPa or above
4. Place the sealing washer (14) and cover plate (13) into position
5. Fit the tap body (8) into the mounting hole making sure first that the flexible hoses (24-25) are firmly tightened into the base of the body
6. Do not use Teflon tape on threads
7. From underneath, apply the washer (15) and horse shoe plate (16) and tighten the mixer onto the basin or benchtop
8. Connect the flexible hoses to the hot and cold isolating stops, hand tighten plus half a turn of the nut to provide a watertight joint
9. Ensure that the hoses are not under tension, twisted or kinked and if bent they have a minimum radius of 30mm
10. Check for leaks

SERVICING - REPLACEMENT OF CARTRIDGE:

1. Remove decorative cover (3) and unscrew the grub screw (2) using an allen key
2. Lift off handle (1) and remove the cartridge dome (4), unscrew brass locking nut (6) and lift out cartridge (7)
3. Replace the cartridge (7), replace the brass locking nut (6), replace the cartridge dome (4) and replace handle (1)
4. Tighten grub screw (2) and push in decorative cover (3)

CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions

Plumbers, please ensure a copy of the Installation Instructions are left with the end user for future reference