

## Mizu Drift Mk2 Sink Mixer Chrome (4\*)

### IMPORTANT NOTE:

Mixer must be installed to the requirements of AS/NZS 3500 by a qualified plumber. Your mixer comes to you already factory assembled and tested. We do not recommend the dismantling of any internal part of the mixer. The mixers are factory tested and sealed so as to give the best performance.

### INSTALLATION INSTRUCTIONS:

1. Flush out new pipe work prior to connecting the new mixer
2. Attach flexible tails to the mixer; connecting the blue labelled hose (25) to the cold 'C' inlet and red labelled hose (24) to the hot 'H' inlet. Tighten the hoses using a shifter.
3. Place the base washer over the sink/bench tap hole
4. Fit the short threaded end of the guide shank (21) from the supplied fixing kit to the bottom of the mixer
5. Pass both the flexible hoses through the top of the tap hole
6. Apply the under mount horse shoe washer (20) and metal plate (19) from the fixing kit to the underside of the tap hole, ensuring the shank is guided through the holes in the washer and metal plate
7. Secure the mixer to the sink/bench by screwing the retaining nut (18) through each shank and securing them against the horse shoe metal plate
8. Fit the hot and cold flexible hoses hose nuts to their corresponding stop valves (Stop valves not supplied with mixer). Ensure both are tightened sufficiently
9. Pressure test the mixer to ensure all connections are free of leaks

**NOTE: Do not over tighten hose tail into the mixer**

**Do not twist hose braiding to tighten hoses**

**Do not use Teflon tape or thread locking compounding on any of the threaded connections**

### CLEANING RECOMMENDATIONS:

We recommend the use of soapy water or approved cleaners. This product should not be cleaned with abrasive materials. Damage caused by any improper treatment is not covered by the product warranty. Refer to Warranty Conditions